



NIGHT OF DESTRUCTION 2020 FIGURE 8 RULES

COMPETING MODELS

This is an OPEN CLASS, any car. NO 3/4 or 1/2 ton pickups, SUV's, Semi Trucks and convertibles (unless covered by a wing).

GENERAL CAR AND BODY REQUIREMENTS

1. Bodies must have doors, roof and quarter panels
2. No weight limit.

DETAILED CAR BODY REQUIREMENTS

1. Windshield and Windows: 1) There is to be no glass on the race car. 2) Full steel wire mesh minimum 1/2-inch to 1-inch square metal in place of windshield is required. No string nets.
2. Fenders optional.
3. Identification and Marking: Numbers must be on both sides of the car and on the roof.
4. Window Ne Mandatory left side door driver window.

FUEL SYSTEM

1. Approved fuel cells recommended.
2. Fuel cells must be securely installed in the trunk compartment, between the frame rails, with two 1-inch wide x 1-inch flat steel straps, both lengthwise and crosswise.
3. Fuel cell must be installed in a minimum 18-gauge sheet metal box strapped in by 1/8-inch by 1-inch steel.
4. Filler spout must remain in the trunk area sealed off from driver.

PERSONAL SAFETY EQUIPMENT AND ROLL BARS

1. General Safety: 1) It is the responsibility of the driver, not Perris Auto Speedway, its officers, or its agents to ensure his/her safety devices and systems are correctly installed, maintained, and properly used at all times.
2. Protective Clothing: A clean full-length fire suit and safety gloves recommended. At a minimum, Long Sleeves, Long Pants, leather gloves and leather boots must be worn at all time. Racing shoes or leather shoes required.
3. Fire Control: Every car must be equipped with one fully charged fire extinguisher having at least a 10B:C rating. The fire extinguisher must be accessible to driver with quick release mount.
4. Helmets: Head and Neck Restraint Devices recommended. Snell approved helmet mandatory, with face shield required. Driver must rely on his own judgment in the selection of any helmet and apparel for durability and safety.

5. Seat Belts: Five-point, quick release restraint system with no less than 3-inches wide recommended. Center crotch belt must be a minimum of 2 inches wide. Belts must be recertified or replaced every 3 years. Both ends must be fastened to roll bar cage with 3/8" grade 5 or better bolts. 4) Belts must be mounted per manufacturer's specifications. At a minimum, a lap and shoulder seat belt is required. No fiberglass, plastic or homemade seats allowed.

6. Roll Bars: A full roll cage is recommended. Must have at least 4 driver door bars and 3 passenger door bars. Steel plate of 1/4 inch must be on drivers door. 3) All roll bars are subject to safety technical inspection and approval. 4) All cage roll bar material must be a minimum of .090 wall steel 1-3/4 inch tubing. No galvanized pipe. Maximum tubing diameter 2-inch. No threaded pipe fittings allowed. 5) All roll bar structure exposed to the driver must be padded with approved padding. The two uprights in the left side door must be padded.

RADIOS:

1. All Demo Cross Drivers must have a one-way radio receiver or radio set to the race/scoring frequency (464.5500).

2. The radios will be used strictly for line-ups and general information from the Scorer's and Race Director only.

3. Radios are to be provided by the Driver.

4. Drivers will not be permitted on the track without a radio and it must be on.

5. Radios along with ear buds can be purchased from **PRE 2.0 Shelly Wooldridge at (951) 295-2997**

PURSE:

1st \$500, 2nd \$300, 3rd \$200